

Differential Pressure Gauge

With Integrated Working Pressure Gauge and Micro Switch

DELTA-comb

Model 702.02.100

Pressure Gauges

- Working pressure gauge integrated as a standard feature enables the central monitoring of differential pressure and working pressure in one measuring instrument
- One or two adjustable microswitches respectively
- High repeatability of the switchpoints
- Differential pressure measuring ranges from 0 ... 250 mbar to 0 ... 25 bar
- High working pressure (static pressure) 25 bar
- Overload value either side 25 bar
- Solid case construction for protection against external mechanical effects
- Integrated pressure equalizing valve as optional extra
- Three cast-on mounting brackets for wall mounting
- Long service life
- Optimal price/performance ratio
- Approval German Lloyd No. 40 146-01HH as optional extra



DELTA-comb with 2 micro switches, terminal box (optional extra) and compression fitting with ferrule (optional extra)

General features

These differential pressure gauges are particularly intended for the monitoring of differential pressures in filter systems, pumps and pipeline systems in the heating, climatic and ventilating technology sector, technical building equipment and in the water management industry.

Apart from the display of the differential pressure, these applications require, as a rule, the display of the current working pressure. For this reason, a working pressure gauge is integrated in the differential pressure gauge **DELTA-comb** as a standard feature. An additional measuring point involving additional expenses for piping and mounting is thus no longer required.

The white dial of the working pressure gauge distinctly stands out against the blue background of the display of the differential pressure gauge, thus enabling a quick and safe reading of both quantities to be measured.

The ranges of 0 ... 250 mbar up to 0 ... 25 bar provide the measuring ranges, which are required in the most different applications. The sturdy and compact design of the differential pressure gauge makes it possible to use it even under tough industrial ambient conditions.

Main applications

- Heating, climatic and ventilating technology
- Dust removing technology
- Technical building equipment
- Filter plants
- Drinking and service water treatment
- Monitoring and control of pumps in pressure boosting and fire extinguishing plants

Suitable for all gaseous and liquid media that will not obstruct the pressure system.

Supplementary data sheets

- Differential pressure gauge with integrated working pressure gauge Model 702.01.100 (see data sheet PM 07.15) **DELTA-plus**
- Differential pressure switch Model 851.02.100 (see data sheet PM 07.17) **DELTA-switch**
- Differential pressure transmitter Model 891.34.2189 (see data sheet PM 07.18) **DELTA-trans**
- Differential pressure gauge with integrated working pressure gauge and micro switch with component approval Model 702.03.100 (see data sheet PM 07.19) **DELTA-plus**

Design and operating principle

Pressure p_1 and p_2 are given in the \oplus and \ominus measuring medium chambers separated by an elastic diaphragm (1).


The differential pressure ($\Delta p = p_1 - p_2$) causes axial movement (measuring travel) of the diaphragm against the measuring range spring (2).

The transmission of the differential pressure proportional to the measuring travel to the movement (4) within the indicating case and to the plungers of the microswitches (5) and is carried out pressure sealed and with little friction by means of a connecting rod (3).

The overpressure protection is provided by contoured metal bolsters for the elastic diaphragm (6).

The adjustment of the switchpoint is made by setpoint screws accessible from the front (7). The assistant scales (8) enable a relatively accurate adjustment of the switchpoints over 270° and indicate the setpoint that is momentarily adjusted.

Illustration of operating principle



Technical data

Nominal size

Differential pressure gauge: \varnothing 100 mm
Working pressure gauge: \varnothing 23 mm

Accuracy class

Differential pressure gauge: 2.5
Working pressure gauge: 4

Scale ranges per EN 837

Differential pressure: 0 ... 0.25 to 0 ... 25 bar
Working pressure: 0 ... 25 bar

Working pressure max. (static pressure)
25 bar

Overpressure safety

Either side max. 25 bar

Operating temperature

Ambient: -10 ... +70 °C
Medium: +90 °C maximum

Ingress protection

IP 54 per EN 60 529 / IEC 529

Measuring media chamber (exposed to pressure medium)

GD-AISI 12 (Cu) 3.2982, black painted

Pressure connections (exposed to pressure medium)

2 x G $\frac{1}{4}$ female, bottom, in-line,
axle base 26 mm

Pressure elements (exposed to pressure medium)

Differential pressure: Compression spring of stainless steel 1.4310
and separating diaphragm of FPM/FKM
fabric back stay (optional NBR)
Working pressure: Bourdon tube Cu-alloy

Links (exposed to pressure medium)

Stainless steel 1.4305, FPM/FKM (optional NBR)

Sealing rings (exposed to pressure medium)

FPM/FKM (optional NBR)

Movement

Cu-alloy, wear parts German silver

Dial

Differential pressure gauge: blue aluminium with white lettering
Working pressure gauge: white plastic with black lettering

Pointer

Differential pressure gauge: white aluminium adjustable pointer
Working pressure gauge: black plastic

Zero adjustment for differential pressure gauge

By means of adjustable pointer

Case

GD-AISI 12 (Cu) 3.2982, black painted

Window

acrylic

Weight

approx. 1.4 kg

Gauge mounting

Pressure entries identified \oplus and \ominus ,
 \oplus high pressure, \ominus low pressure.
Mounting by means of rigid tailpipes or wall mounting with
mounting brackets

Electrical contact


Contact type	Micro switch	
Contact functions	1 x SPDT	2 x SPDT
	850.3	850.3.3

Load data	Voltage AC	Voltage DC	
	U max.	250 V	30 V
	I max.	5 A	0.4 A
	P max.	250 VA	10 W
Switching point adjustment	from the outside at assistant scale by means of setpoint screw(s)		
Setting range	from 10 % to 100 % of span		
Switching point repeatability accuracy	≤ 1.6 %		
Contact hysteresis	max. 5 % of full scale value (optional 2.5 % max.)		
Wiring	Cable gland M20x1.5 with 1 m connected cable		


Optional extras

- Pressure media chamber GD-AISI 12 (Cu) HART-COAT surface protection
- Pressure media chamber of stainless steel (without working pressure gauge)
- Accuracy class 1.6 for differential pressure gauge with factory-set switching points for ranges from 0 ... 1 bar to 0 ... 25 bar (switching direction to be specified)
- Ingress protection IP 65
- Integrated pressure equalizing valve (stainless steel and FPM/FKM)
- 4-way valve manifold Cu-alloy or stainl. steel (1x press. equalising valve, 2x pressure gauge valve, 1x valve for purging or air bleeding)
- Other threaded pressure connections female or male
- Compression fitting with ferrule for pipe \varnothing 6, 8 or 10 mm
- Front flange for panel mounting
- Wiring with terminal box, cable gland M20x1.5 or L-plug


Dimensions in mm




2123 568.01



Electrical connection details




Integrated pressure equalizing valve as optional extra




2261 804.01

4-way valve manifold as optional extra




2261 821.03

Panel mounting as optional extra




2157 306.02

Wiring versions as optional extra



Electrical connection details



2162 679.01

Ordering information for Differential Pressure Gauge with integrated working pressure gauge and micro switch

DELTA-comb Model 702.02.100

Field No.	Code	Instrument design	
1		Unit	
	B	bar	
	?	other	
			<i>Please state as additional text</i>
			Measuring range
	AN	0 ... 0.25 bar	
	BB	0 ... 0.4 bar	
	BC	0 ... 0.6 bar	
	BD	0 ... 1 bar	
	BE	0 ... 1.6 bar	
BF	0 ... 2.5 bar		
BG	0 ... 4 bar		
BH	0 ... 6 bar		
BI	0 ... 10 bar		
BK	0 ... 16 bar		
BL	0 ... 25 bar		
2	??	other	
		<i>Please state as additional text</i>	

Field No.	Code	Instrument design	
		Process connection	
	AA	2 x G 1/4 female <i>standard</i>	
	AM	2 x G 1/4 B Cu-alloy	
	AN	2 x G 1/4 B stainless steel	
	DA	compression fitting with ferrule, steel for pipe Ø 6 mm	
	DB	compression fitting with ferrule, steel for pipe Ø 8 mm	
	DC	compression fitting with ferrule, steel for pipe Ø 10 mm	
	DE	compression fitting with ferrule, stainless steel for pipe Ø 6 mm	
	DF	compression fitting with ferrule, stainless steel for pipe Ø 8 mm	
	DG	compression fitting with ferrule, stainless steel for pipe Ø 10 mm	
	DK	compression fitting with ferrule, Cu-alloy for pipe Ø 6 mm	
	DL	compression fitting with ferrule, Cu-alloy for pipe Ø 8 mm	
	DM	compression fitting with ferrule, Cu-alloy for pipe Ø 10 mm	
3	??	other <i>Please state as additional text</i>	
		Pressure media chamber	
	A	aluminium, black painted <i>standard</i>	
	H	aluminium HART-COAT	
	C	stainless steel, without working pressure gauge	
4	?	other <i>Please state as additional text</i>	
		Separation diaphragm / Sealing rings	
	J	FPM/FKM <i>standard</i>	
5	G	NBR	
		Accuracy class for differential pressure gauge	
	4	class 2.5 <i>standard</i>	
6	3	class 1.6 <i>scale ranges 0 ... 1 bar and up ¹⁾</i>	
		Mounting flange / bracket	
	Z	without <i>standard</i>	
	D	front flange, black steel	
7	?	other <i>Please state as additional text</i>	
		Ingress protection	
	F	IP 54 <i>standard</i>	
8	I	IP 65	
		Alarm contacts	
	E	1 SPDT micro switch 850.3 <i>standard</i>	
9	D	2 SPDT micro switches 850.3.3	
		Wiring	
	1	cable gland M20 x 1.5 with 1 m connected cable <i>standard</i>	
	P	terminal box M20 x 1.5	
	G	L-plug 3-pin + PE <i>(with 1 contact)</i>	
	N	L-plug 6-pin + PE <i>(with 2 contacts)</i>	
10	?	other <i>Please state as additional text</i>	
		Valve manifold / Pressure equalizing valve	
	Z	without <i>standard</i>	
	I	integrated pressure equalizing valve	
	M	4-way valve manifold, Cu-alloy	
11	V	4-way valve manifold, stainless steel	
		Approvals	
	Z	without <i>standard</i>	
	G	with GL-approval	
12	V	component-approved (flow protection DIN 32 727 and VdTÜV note of instructions "flow 100")	
		Additional order details	
	YES	NO	
13	1	Z	quality certificates <i>Please state in clearly understandable text !</i>
14	T	Z	additional text <i>Please state in clearly understandable text !</i>

1) with factory-set contacts, please specify switching points and switching direction as additional text

Order code for DELTA-comb Model 702.02.100

	1	2	3	4	5	6	7	8	9	10	11	12	13	14
702.02-E	-	<input type="text"/>	-	<input type="text"/>	-	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	-	<input type="text"/>

Additional text: _____

Specifications and dimensions given in this leaflet represent the state of engineering at the time of printing. Modifications may take place and materials specified may be replaced by others without prior notice.



WIKA Alexander Wiegand GmbH & Co. KG
 Alexander-Wiegand-Straße · 63911 Klingenberg
 Tel.: (0 93 72) 132-0 · Fax: (0 93 72) 132-406
 http://www.wika.de · E-mail: info@wika.de