

# COMPRESSION HEAD

## KUDOS USA HYDRAULIC CRIMPERS H-412HE

### ■ Model No. **UB-412HE**

Length : 258 mm  
Weight : 4.2 kgs

### ■ Specifications:

Max. Pressure : 700 bar  
Oil Required : 53 cc  
Max. Output : 11.6 tons / 114 kN  
Jaw Opening : 32mm

### ■ Crimping Capacity:

- Max. Compression : 400mm<sup>2</sup> copper lugs
- Accepts all dies used for Alcoa, Burndy, T&B, Klauke, Cembre and Blackburn 12-ton compressors
- Dies sold separately (See page 151)  
(CU16/25/35/50/70/95/120/150/185/240/300/400)

### ■ Features:

- C-frame has open jaw for easy access to the fitting.
- Operated by any hydraulic pump with rated oil pressure of 700 bar (10,000 psi).
- Single action cylinder with spring return.
- Dies are easy to change.
- Crimping capacity identical to UB-412 tool. (See page 122 ~ 123)

### ■ Accessories:

Plastic carrying case



### ■ Model No. **H-412HE**

Length : 335 mm  
Weight : 4.3 kgs

### ■ Specifications:

Max. Pressure : 700 bar  
Oil Required : 53 cc  
Max. Output : 11.6 tons / 114 kN  
Jaw Opening : 32mm

### ■ Crimping Capacity:

- Max. Compression : 400mm<sup>2</sup> copper lugs
- Accepts all dies used for Alcoa, Burndy, T&B, Klauke, Cembre and Blackburn 12-ton compressors
- Dies sold separately (See page 151)  
(CU16/25/35/50/70/95/120/150/185/240/300/400)

### ■ Features:

- C-frame has open jaw for easy access to the fitting.
- Operated by any hydraulic pump with rated oil pressure of 700 bar (10,000 psi).
- Single action cylinder with spring return.
- Handle grip for easy carrying.
- Crimping capacity identical to UB-412 tool. (See page 122 ~ 123)
- Dies are easy to change.

### ■ Accessories:

Plastic carrying case



※ Crimping without die sets is prohibited.



## KUDOS USA HYDRAULIC CRIMPERS H-412HE