

CUTTERS

KUDOS USA HYDRAULIC CUTTERS HYSC-20

■ Model No. **HYSC-20**

Length : 344 mm
Weight : 2.5 kgs

■ Specifications:

Max. Pressure : 700 bar
Oil Required : 22 cc
Max Output : 5.3 tons / 52 kN

■ Cutting Capacity:

Wire rope 6x7 : 16 mm
Wire rope 6x12 : 20 mm
Wire rope 6x19 : 20 mm
Soft copper bar : 20 mm
Soft aluminum bar : 16 mm
Underground cable : 18 mm
Soft steel bar : 16 mm
Reinforcing rod : 13 mm
Cu strands : 20 mm
Al strands : 20 mm
ACSR : 21 mm
Guy wire 1x7 : 15 mm
Guy wire 1x19 : 16 mm
Cutting of piano wire is prohibited.

■ Features:

- 180° rotating head for convenient operation.
- Superior guillotine type cutting for less jamming than shear type cutters.
- Single stage pumping action.
- All blades are easily replaceable.
- Flip-top latch for easy insertion of cutting material.
- Single stage pump action with spring return.
- No set-up time required.
- Lightweight, self-contained tool, can be used anywhere.

■ Accessories:

Carrying Bag



KUDOS USA HYDRAULIC CUTTERS HYSC-20

HYSC-20 #64	Moving Blade
HYSC-20 #55	Fixed Blade



KUDOS USA HYDRAULIC CUTTERS HYSC-20