

KUDOS USA HYDRAULIC CUTTERS HYSC-24

■ **Model No. HYSC-24**

Length : 360 mm

Weight : 2.7 kgs

■ **Specifications:**

Max. Pressure : 700 bar

Oil Required : 25 cc

Max. Output : 6.7 tons / 66 kN

■ **Cutting Capacity:**

Wire rope 6x7 : 24 mm

Wire rope 6x12 : 24 mm

Wire rope 6x19 : 24 mm

Soft copper bar : 23 mm

Soft aluminum bar : 24 mm

Soft steel bar : 16 mm

Cu strands : 24 mm

Al strands : 24 mm

ACSR : 24 mm

(Note : Tensile strength (daN/mm²) ≤ 180)

Cutting of plano wire is prohibited.



■ **Features:**

- 180° rotating head for convenient operation.
- Superior guillotine type cutting for less jamming than shear type cutters.
- Single stage pumping action.
- All blades are easily replaceable.
- Flip-top latch for easy insertion of cutting material.
- Single stage pump action with spring return.
- No set-up time required.
- Lightweight, self-contained tool, can be used anywhere.

■ **Accessories:**

Carrying Bag



KUDOS USA HYDRAULIC CUTTERS HYSC-24

HYSC-24 #11	Moving Blade
HYSC-24 #3	Fixed Blade

