BATTERY OPERATED TOOLS



KUDOS USA BATTERY OPERATED TOOLS / CRIMPER BATTERY TYPE K-BGD3

■ Model No. K-BGD3 (with Li-ion Battery & Charger)

Length : 459 mm / Wt.: 3.0 kgs(w/o battery) Weight : 3.4 kgs (2.0Ah battery included)

Specifications:

Drive unit:18V DC Motor Charger (GS/CE): voltage : 110V Single Phase AC Input voltage : 230V Single Phase AC Input Input frequency : 50-60 Hz Reservoir capacity : 40 cc

Crimping Capacity:

Max. Pressure : 460 bar : 6 tons / 58 kN Max. Output

Features:

- Proper crimps are assured with butting steel jaws.
- · Increased strength and greater bearing area is provided with larger steel bolts.
- · Fast, easy, one-hand die insertion.
- · No lost dies with spring loaded positive lock die retainer buttons.
- · Full crimp force assured with over center cam action.
- · Operator protection provided with butt stops and heat shrinktubing.
- · Long life expectancy provided with fiberglass handles and light weight high strength aluminum alloy castings.
- . The "D3" groove accommodates the line of type "W"-die inserts.

Connector Range:

- Copper, Aluminum, ACSR, Copperweld, Alumoweld, Steel, S201, 5005, Compressed and Compact conductors. • Copper Taps: # 10 sol.-2/0 str. • Aluminum,ACSR Taps: # 14 sol. -4/0 ACSR • Stimups: # 6 ACSR-4/0 ACSR

- Overhead Full Tension Deedend, Full Tension Splices, Non Tension Splices, and Terminals Conductor Range: # 10 str. -4/0 ACSR
- Code conductor connectors: # 8-4/0 str. Copper and Aluminum

KuDos KW-diss	Burndy W-Dise	KuDos KW-dies	Burndy W-Die
KW-BG	W-BG	KW-165	W-165
KW-O	W-O	KW-166	W-166
KW-C	W-C	KW-171	W-171
KW-K840	W-K840	KW-237	W-237
KW-161	W-161	KW-243	W-243
KW-162	W-162	KW-247	W-247
KW-163	W-163	KW-249	W-249
KW-164	W-164	KW-702	W-702



KUDOS USA BATTERY OPERATED TOOLS / CRIMPER BATTERY TYPE K-BGD3



